

SYSTEM 3000 - CITRUS

K225

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code K225

Manufacturer : Selden Research Limited
Staden Lane Business Park, Staden Lane,
Buxton, Derbyshire. SK17 9RZ
United Kingdom

Product Name SYSTEM 3000 - CITRUS

Tel : 01298 26226
Fax : 01298 26540
Email : sales@selden.co.uk

2 HAZARDS IDENTIFICATION

R12 Extremely flammable., R43 May cause sensitisation by skin contact.

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

Classification R43. F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
2,4-dimethylcyclohexene-3-carbaldehyde	268-264-1	68039-49-6	< 1%	Xi;R36/38. R43,R52/53.
BUTANE	203-448-7	106-97-8	30 - 60%	F+;R12
CITRAL	226-394-6	5392-40-5	1 - 5%	R43 Xi;R38
geraniol	203-377-1	106-24-1	< 1%	Xi;R38,R41. R43.
PROPAN-2-OL	200-661-7	67-63-0	5 - 10%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION	Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical attention., For breathing difficulties oxygen may be necessary.
INGESTION	Rinse mouth thoroughly., Drink plenty of water., Get medical attention.
SKIN CONTACT	Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.
EYE CONTACT	Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA	Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES	Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSION HAZARDS	Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses

7 HANDLING AND STORAGE

USAGE PRECAUTIONS	Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
USAGE DESCRIPTION	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm 1810 mg/m3
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm 1250 mg/m3
ENGINEERING MEASURES	Provide adequate general and local exhaust ventilation.			
EYE PROTECTION	Eye protection should be considered when changing aerosols in dispensing unit.			
OTHER PROTECTION	General workwear only			

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol
ODOUR	Characteristic, Citrus
PHYSICAL DATA COMMENTS	Information given relates to total aerosol container contents.
RELATIVE DENSITY	0.6 @ 20 °C
pH-VALUE, CONC. SOLUTION	N/A
FLASH POINT (°C)	- 74

AUTO IGNITION TEMPERATURE (°C) + 405
 FLAMMABILITY LIMIT - LOWER(%) 1.8
 FLAMMABILITY LIMIT - UPPER(%) 10.0

10 STABILITY AND REACTIVITY

STABILITY Stable under normal temperature conditions., Avoid:., Heat, sparks, flames.

CONDITIONS TO AVOID Avoid heat, flames and other sources of ignition., Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

HAZARDOUS DECOMPOSITION PRODUCTS Fire creates:., Toxic gases/vapours/fumes of:., Carbon monoxide (CO)., Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.

SKIN CONTACT Liquid may irritate skin.

EYE CONTACT Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UN NO. ROAD 1950

UK ROAD CLASS 2.1

ADR CLASS NO. 2.1

PROPER SHIPPING NAME AEROSOLS, FLAMMABLE

UN NO. SEA 1950

IMDG CLASS 2.1

AIR CLASS 2.1

15 REGULATORY INFORMATION

LABELLING



Irritant (Xi) Extremely Flammable (F+)

CONTAINS CITRAL, geraniol, 2,4-dimethylcyclohexene-3-carbaldehyde

RISK PHRASES R12 Extremely flammable., R43 May cause sensitisation by skin contact.

SAFETY PHRASES S16 Keep away from sources of ignition - No smoking., S2 Keep out of the reach of children, S51 Use only in well-ventilated areas.

STATUTORY INSTRUMENTS Control of Substances Hazardous to Health., Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION The following risk phrases relate to the raw materials in the product and not the product itself:-

REVISION DATE 27/07/2010

REV. NO./REPL. SDS GENERATED 7

RISK PHRASES IN FULL R12 Extremely flammable.| R11 Highly flammable., R36 Irritating to eyes., R67 Vapours may cause drowsiness and dizziness.| R38 Irritating to skin., R43 May cause sensitisation by skin contact.| R38 Irritating to skin., R43 May cause sensitisation by skin contact., R41 Risk of serious damage to eyes.| R43 May cause sensitisation by skin contact., R36/38 Irritating to eyes and skin., R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.|